



ERNST FLOW INDUSTRIES
A CLARK-RELIANCE COMPANY



NOTE: Always wear Safety Glasses when working with Gauge Glass.

EFI HIGH PRESSURE CLEAR – Model #500

TEMPERATURE & PRESSURE RATINGS

Maximum Recommended Working Pressure, PSI

SIZE	LENGTH	TEMPERATURES UP TO 150°F NO CORROSION	STEAM BOILER SERVICE UP TO 425°F	
1/2" O.D. +0, -1/32"	8"	460	340	
	10"	445	335	
	12"	435	325	
	14"	415	315	
	16"	400	300	
	18"	385	295	
	20"	375	285	
	24"	340	270	
	30"	295	***	
	36"	260	***	
5/64" Wall ± 1/64"	48"	205	***	
	60"	155	***	
	72"	110	***	
	5/8" O.D. +0, -1/32"	8"	435	320
		10"	420	315
		12"	410	305
		14"	390	295
		16"	375	285
		18"	360	280
		20"	350	270
24"		320	255	
30"		280	***	
36"		245	***	
3/32" Wall ± 1/64"	48"	195	***	
	60"	150	***	
	72"	100	***	
	3/4" O.D. +0, -1/32"	8"	425	315
		10"	410	310
		12"	400	300
		14"	385	290
		16"	370	280
		18"	355	275
		20"	345	265
24"		315	250	
30"		275	***	
36"		240	***	
7/64" Wall ± 1/64"	48"	190	***	
	60"	145	***	
	72"	100	***	

*** Maximum recommended length in this service is 24".

TUBULAR GAUGE GLASS (TEMPERATURE & PRESSURE RATINGS)

EFI HIGH PRESSURE CLEAR – Model #500 (cont.)

TEMPERATURE & PRESSURE RATINGS

		Maximum Recommended Working Pressure, PSI		
SIZE	LENGTH	TEMPERATURES UP TO 150°F NO CORROSION	STEAM BOILER SERVICE UP TO 425°F	
7/8" O.D. +0, -1/32"	8"	380	This size Not Recommended in this Service	
	10"	370		
	12"	360		
	14"	350		
	16"	340		
	18"	335		
	20"	330		
	24"	315		
	30"	285		
	36"	265		
1/8" Wall ± 1/32"	48"	210		
	60"	160		
	72"	110		
	1" O.D. +0, -1/32"	8"	345	This size Not Recommended in this Service
		10"	335	
		12"	325	
		14"	320	
		16"	310	
		18"	305	
		20"	300	
24"		285		
30"		260		
36"		240		
1/8" Wall ± 1/32"	48"	190		
	60"	145		
	72"	100		
	1-1/8" O.D. +0, -3/64"	8"	270	This size Not Recommended in this Service
		10"	265	
		12"	260	
		14"	250	
		16"	245	
		18"	240	
		20"	240	
24"		235		
30"		225		
36"		200		
1/8" Wall ± 1/32"	48"	180		
	60"	150		
	72"	130		
	1-1/4" O.D. +0, -3/64"	8"	240	This size Not Recommended in this Service
		10"	235	
		12"	230	
		14"	225	
		16"	220	
		18"	215	
		20"	215	
24"		210		
30"		200		
36"		180		
1/8" Wall ± 1/32"	48"	160		
	60"	135		
	72"	115		
	1-1/2" O.D. +0, -3/64"	8"	210	This size Not Recommended in this Service
		10"	205	
		12"	200	
		14"	200	
		16"	195	
		18"	190	
		20"	190	
24"		185		
30"		175		
36"		160		
1/8" Wall ± 1/32"	48"	140		
	60"	120		
	72"	100		

*** Maximum recommended length in this service is 24".

EFI HIGH PRESSURE RED LINE – Model #501

TEMPERATURE & PRESSURE RATINGS

		Maximum Recommended Working Pressure, PSI		
SIZE	LENGTH	TEMPERATURES UP TO 150°F NO CORROSION	STEAM BOILER SERVICE UP TO 425°F	
1/2" O.D. +0, -1/32"	8"	390	300	
	10"	370	295	
	12"	360	295	
	14"	345	290	
	16"	335	285	
	18"	325	280	
	20"	310	280	
	24"	280	270	
	30"	250	***	
	36"	215	***	
5/64" Wall ± 1/64"	48"	175	***	
	60"	135	***	
	72"	100	***	
	5/8" O.D. +0, -1/32"	8"	370	285
		10"	345	280
		12"	335	280
		14"	325	275
		16"	315	270
		18"	305	265
		20"	290	265
24"		265	255	
30"		235	***	
36"		205	***	
3/32" Wall ± 1/64"	48"	165	***	
	60"	125	***	
	72"	90	***	
	3/4" O.D. +0, -1/32"	8"	360	280
		10"	340	275
		12"	330	275
		14"	320	270
		16"	310	265
		18"	300	260
		20"	285	260
22"		270	250	
24"		260	250	
30"		230	***	
7/64" Wall ± 1/64"	36"	200	***	
	48"	160	***	
	60"	125	***	
	72"	90	***	
	1-1/4" O.D. +0, -3/64"	8"	315	This size Not Recommended in this Service
		10"	310	
		12"	305	
		14"	300	
		16"	285	
		18"	280	
20"		275		
24"		265		
30"		240		
36"		225		
1/8" Wall ± 1/32"	48"	185		
	60"	145		
	72"	100		
	1-1/2" O.D. +0, -3/64"	8"	275	This size Not Recommended in this Service
		10"	270	
		12"	265	
		14"	260	
		16"	250	
		18"	245	
		20"	240	
24"		230		
30"		210		
36"		195		
1/8" Wall ± 1/32"	48"	160		
	60"	125		
	72"	90		

*** Maximum recommended length in this service is 24".

EFI HIGH PRESSURE HEAVY WALL CLEAR & RED NE Model #600 & 601

TEMPERATURE & PRESSURE RATINGS

Maximum Recommended Working Pressure, PSI

SIZE	LENGTH	TEMPERATURES UP TO 150°F NO CORROSION	STEAM BOILER SERVICE UP TO 425°F
5/8" O.D. +1/64, -3/64"	8"	600	350
	10"	600	345
	12"	600	340
	14"	600	335
	16"	600	325
3/16" Wall +3/64", -0	18"	600	320
	20"	600	315
	24"	580	300
	30"	550	***
	36"	500	***
	48" (Max.)	340	***
3/4" O.D. +1/64, -3/64"	8"	600	350
	10"	600	345
	12"	600	340
	14"	600	335
	16"	600	325
7/32" Wall +1/16", -0	18"	600	320
	20"	600	315
	24"	580	300
	30"	550	***
	36"	500	***
	48" (Max.)	340	***
7/8" O.D. +1/64, -3/64"	8"	600	350
	10"	600	345
	12"	600	340
	14"	600	335
	16"	600	325
1/4" Wall +1/16", -0	18"	600	320
	20"	600	315
	24"	580	300
	30"	550	***
	36"	500	***
	48" (Max.)	340	***
1" O.D. +1/64, -3/64"	8"	600	350
	10"	600	345
	12"	600	340
	14"	600	335
	16"	600	325
5/16" Wall +1/16", -0	18"	600	320
	20"	600	315
	24"	580	300
	30"	550	***
	36"	500	***
	48" (Max.)	340	***

*** Maximum recommended length in this service is 24".



ERNST FLOW INDUSTRIES
A CLARK-RELIANCE COMPANY

16633 FOLTZ PARKWAY
STRONGSVILLE, OH 44149
TEL 732-938-5641
FAX 732-938-9463
WWW.ERNSTFLOW.COM
INFO@ERNSTFLOW.COM