



MODEL NUMBER EA100G-300

NOTES:

1. MICRO SWITCH APPROVED FOR THE FOLLOWING RATINGS:
5A-125, 250, OR 480 VAC
1/2A - 125 VDC
1/4A - 250 VDC
2. UNITS IN INCHES W/ MM EQUIVALENTS IN BRACKETS
3. MINIMUM SG. = .799
4. MAWP PER B16.5 GROUP 1.1 300 CLASS FLANGE
5. HYDROTEST PRESSURE 750 PSIG.
6. UNIT WEIGHT: 65 LB (29.5 KG)
7. BODY MATERIAL: SA216 WCB

DESIGN PRESSURE/TEMPERATURE: 500 PSIG / 483°F

REPLACEMENT PARTS				
NO	PART NO.	DESCRIPTION	DRAWING	QTY.
1	REA6-14X	SWITCH: ALL MODELS	EA1351	1
2	REA7235	FLOAT	EA1344	1
3	V19376 3 9 2	FLANGE GASKET SPIRAL WOUND	V-19376	1
16	X172162	SCREW HHCS 3/4-10 X 2-3/4" B7	X-172162	8
19	X172883	SCREW: 8-32 X 7/16": BHCS	X-172883	3

MANUFACTURED BY
Clark-Reliance®
16633 FOLTZ PARKWAY
STRONGSVILLE, OH 44149 USA
(440) 572-1500 | www.clarkreliance.com
© Clark-Reliance® Corporation. All Rights Reserved.

RELIANCE®

LIQUID LEVELARM ASSEMBLY: 300#: EA100G

PART NUMBER: EA1353M
TOLERANCE CLASS (PER PES-004): D
MATERIAL: SEE BOM
REVISION: 0
DRAWN: NK
CHECKED: JK
DATE: 8/30/2017
DRAWING NO.: EA1353M
REV.: 0

REV	DATE	REVISION	BY
0	3/3/2017	LIQUID LEVELARM ASSEMBLY: 300#: EA100G, NR CDC 15-112	

THIS DRAWING CONTAINS MATERIAL THAT IS CONFIDENTIAL AND/OR PRIVILEGED FOR THE SOLE USE OF THE INTENDED RECIPIENT. ANY REVIEW, RELIANCE OR DISTRIBUTION BY OTHERS OR FORWARDING WITHOUT EXPRESS PERMISSION IS STRICTLY PROHIBITED.